## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Sources				
Supplier's name	e or trade mark:	Hera GmbH & Co K	G	
Supplier's addre	ess: FE, Dieselstr	aße 9, 32130 Enger	Herford, DE	
Model identifie	r: LED Spot			
Type of light so	urce:			
Lighting technol	logy used:	LED	Non-directional or directional:	DLS
Light source cap-type		nein		
(or other electri	ic interface)			
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein
Colour-tuneable light source:		Nein	Envelope:	-
High luminance	light source:	Nein		
Anti-glare shield	d:	Nein	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	T	T
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		3	Energy efficiency class	G
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		150 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000 or 4 000
On-mode power (P <sub>on</sub> ), expressed in W		3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer	Height	325	Spectral power	See image
dimensions	Width	32	distribution in the	in last page
without	Depth	15		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,444			
		coordinates (x and y)	0,408			
Parameters for directional light sources:						
Peak luminous intensity (cd)	1	Beam angle in	38			
		degrees, or the				
		range of beam				
		angles that can be				
		set				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	0	Survival factor	0,00			
the lumen maintenance factor	0,00					

(a)'-': not applicable; (b)'-': not applicable;

