

Material Safety Data Sheet (MSDS)

Product Name: Lithium-ion rechargeable cell

Model Number: INR18650/25P

Applicant: EVE Energy Co.,Ltd.

Address: No.38, HuiFeng 7th Road, Zhongkai Hi-Tech

Zone, Huizhou, Guangdong, China

KeySense Testing & Certification International Co., Ltd. 21-3F, Lab Building, No.29 District, ZhongKai Hi-Tech Industrial Development Park,

Huizhou, Guangdong, China



Section 1. PRODUCT AND COMPANY IDENTIFICATION

Product Details

Product Name: Lithium-ion rechargeable cell **Product Use:** Used in portable applications

Model: INR18650/25P

Supplier Name: EVE Energy Co.,Ltd.

No.38, HuiFeng 7th Road, Zhongkai Hi-Tech Zone, Supplier Address:

Huizhou, Guangdong, China

Supplier Phone

+86-752-2606966 Number:

Emergency telephone

+86-752-2606966 number:

Section 2. COMPOSITION / INFORMATION ON INGREDIENTS

In our dis of Nove	OAO Na	Dama and a f O and and (0/)
Ingredient Name	CAS No.	Percent of Content (%)
Lithium nickel cobalt		
manganese	346417-97-8	36
oxide(LiNi $_x$ Co $_y$ Mn $_{1-x-y}$ O $_2$)		
Graphite	7782-42-5	18
Ethylene carbonate	96-49-1	5
Dimethyl carbonate	616-38-6	8
Phosphate(1-),hexafluoro- ,lithium	21324-40-3	5
Polyvinylidene fluoride	24937-79-9	2
Copper	7440-50-8	16
Aluminum	7429-90-5	10

Remark:

Phosphate(1-),hexafluoro-,lithium (CAS No.21324-40-3)

Synonym: Lithium Salt (LiPF6)

Section 3. HAZARDS IDENTIFICATION





Hazard description: Harmful! Do not short circuit, recharge, puncture, incinerate, crush, immerse, force discharge or expose to temperatures above the declared operating temperature range of the product. Risk of fire or explosion.

Under normal conditions of use, the electrode materials and liquid electrolyte they contain are

Date of Issue: May.10.2019 Page 2 of 7



not exposed to the outside, provided the battery integrity is maintained and seals remain intact. Risk of exposure only in case of abuse (mechanical, thermal, electrical) which leads to the activation of safety valves and/or the rupture of the battery containers. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/explosion/fire may follow, depending upon the circumstances.

Section 4. FIRST-AID MEASURES

Irrigate thoroughly with water for at least 15 minutes. Obtain medical

attention.

Skin: Wash off skin thoroughly with water. Remove contaminated clothing

and wash before reuse. In severe cases obtain medical attention.

Inhalation: Remove from exposure, rest and keep warm. In severe cases obtain

medical attention.

Ingestion: Wash out mouth thoroughly with water and give plenty of water to

drink. Obtain medical attention.

Further treatment: All cases of eye contamination, persistent skin irritation and

casualties who have swallowed this substance or been affected by

breathing its vapours should be seen by a Doctor.

Section 5. FIRE-FIGHTING MEASURES

Hazardous Combustion When burned, hazardous products of combustion including fume of

Products: carbon monoxide and carbon dioxide can occur.

Extinguishing Media: Water, carbon dioxide, dry chemical or foam.

Basic Fire Fighting

Procedures:

Wear NIOSH/MSHA approved positive pressure self-contained

breathing apparatus and protective clothing to prevent contact with

skin and eyes.

Section 6. ACCIDENTAL RELEASE MEASURES

Accidental: If the battery breakage and electrolyte leakage, evacuate personnel

until the smoke cleared.

Wipe with a cloth and placed in steel drums into the bag inside. If the battery is hot, away from the scene firstly, cool the battery, so

that the steam dissipated. Adequate ventilation.

Avoid skin or eye contact steam.

Waste treatment: The battery Should discharge completely, the waste batteries will be

turned over in the relevant sector, and all waste must refer to the United Nations, national, local regulations for disposal. Reference to

national or federal Environmental Protection Agency EPA.

Date of Issue: May.10.2019 Page 3 of 7



Section 7. HANDLING AND STORAGE

Prohibit mechanical or electrical damage battery.

Stored in a dry, cool and ventilated environment, to avoid temperature changes or high temperature.

Keep away from heat, avoid prolonged sun exposure.

Against short circuit, overcharge, forced discharge, or in a fire.

Battery disassembly, crush, fire or high temperatures can cause fire or explosion, prohibit short-circuit or error operation.

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection: If the battery leaks, the need for full ventilation.

Hand Protection: Under normal use, do not.Personal Protection: Under normal use, do not.Other protection: Under normal use, do not.

If the battery leaks, must wear the following protection products.

	Respiratory protection	In all fire situations, use self-contained breathing apparatus.
m m	Hand protection	In the event of leakage wear gloves.
	Eye protection	Safety glasses are recommended during handling.
	Other	In the event of leakage, wear chemical apron.

Date of Issue: May.10.2019 Page 4 of 7



Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Nominal Voltage: 3.6V

Capacity: 2500mAh

Watt-hour: 9Wh **Appearance characters:** Green

Section 10. STABILITY AND REACTIVITY

Product is stable under conditions described in Section 7.

Hazardous reactions may occur under some specific conditions.

Conditions to avoid: When a battery cell is exposed to an external short-circuit, crushes,

> modification, high temperature above 100 degree C, it will be the cause of heat generation and ignition. Avoid to be exposed to direct

sunlight and high humidity.

Conductive materials, water, seawater, strong oxidizers and strong

acids.

Hazardous

Materials to avoid:

decomposition Acrid or harmful gas is emitted during fire.

products:

Section 11. TOXICOLOGICAL INFORMATION

Primary irritant effect: None, unless battery ruptures. In the event of exposure to internal

> contents, corrosive fumes will be very irritating to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-

fibrotic lung injury and membrane irritation.

Inhalation: Lung irritant. Skin contact: Skin irritant Eye irritant. **Eye contact:**

Tissue damage to throat and gastro-respiratory tract if swallowed. Ingestion:

Medical conditions

generally aggravated by

exposure:

In the event of exposure to internal contents, eczema, skin allergies,

lung injuries, asthma and other respiratory disorders may occur.

Section 12. ECOLOGICAL INFORMATION

Environmental Impact: Proper use and disposal of the battery will not harm the environment.

Dispose of the battery, away from water, rain and snow.

Date of Issue: May.10.2019 Page 5 of 7



Section 13. DISPOSAL CONSIDERATIONS

Do not incinerate, or subject cells to temperatures in excess of 100 ℃. Such abuse can result in loss of seal, leakage, and/or cell explosion.

Waste disposal must be in accordance with the applicable regulations. Disposal of the lithium ion battery cells should be performed by permitted, professional disposal page: firms knowledgeable in state or local requirements of hazardous waste treatment and hazardous waste transportation. Incineration should never be performed by battery but users, eventually by trained professional in authorized facility with proper gas and fume treatment.

Section 14. TRANSPORT INFORMATION

According to PACKING INSTRUCTION 965 ~ 967 of IATA DGR 60th Edition for transportation, the special provision 188 of IMDG (inc Amdt 38-16). The batteries should be securely packed and protected against short-circuits. Examine whether the package of the containers are integrate and tighten closed before transport. Take in a cargo of them without falling, dropping, and breakage. Prevent collapse of cargo piles. Don't put the goods together with oxidizer and chief food chemicals. The transport vehicle and ship must be cleaned and sterilized otherwise it is not allowed to assemble articles. During transport, the vehicle should prevent exposure, rain and high temperature. For stopovers, the vehicle should be away from fire and heat sources. When transported by sea, the assemble place should keep away from bedroom and kitchen, and isolated from the engine room, power and fire source. Under the condition of Road Transportation, the driver should drive in accordance with regulated route, don't stop over in the residential area and congested area. Forbid to use wooden, cement for bulk transport.

(a) UN number 3480&3481

LITHIUM ION BATTERIES (including lithium ion polymer

batteries) or;LITHIUM ION BATTERIES CONTAINED IN

(b) UN Proper shipping name EQUIPMENT or LITHIUM ION BATTERIES PACKED

WITH EQUIPMENT (including lithium ion polymer

batteries)

(c) Transport hazard class(es)

9

(d) Packing group (if applicable)

Ш

(e) Marine pollutant (Yes/No)

(g) Special precautions

No information available.


(f) Transport in bulk (according to Annex II of MARPOL 73/78 and the

IBC Code)

No information available.

Transport fashion: By air, by sea, by railway, by road.

Date of Issue: May.10.2019 Page 6 of 7





Section 15. REGULATORY INFORMATION

《Dangerous Goods Regulation》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

OSHA Hazard Communication Standard Status

Toxic Substances Control Act (TSCA) Status

SARA Title III

RCRA

In accordance with all Federal, State and Local laws

Section 16. OTHER INFORMATION

The above information is based on the data of which we are aware and is believed to be correct as of the data hereof. Since this information may be applied under conditions beyond our control and with which may be unfamiliar and since data made available subsequent to the data hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

Date of Issue: May.10.2019 Page 7 of 7