

**Keppower Li Ion Rechargeable Battery
Protected 14430 3.6V 1300mAh (P1443C4)**

| No. | Item | Details | Remarks |
|------|---|--|--------------------|
| 1.1 | Product Name | Keppower Protected 14430 3.6V 1300mAh (P1443C4) | |
| 1.2 | Supplier | Keppower Technology Co., Limited | |
| 1.3 | Cell | China 14430 3.6V 1300mAh | |
| 1.4 | Capacity | Min. 1200mAh; Normal: 1300mAh | Discharge:0.2CmA |
| 1.5 | Normal Volatge | 3.60V | |
| 1.6 | Stanard Charge voltage | 4.20V | |
| 1.7 | Standard Charge current | 650mA | |
| 1.8 | Charge Time(Std.) | 4 hours | |
| 1.9 | Standard Discharge Cut-off Voltage | 2.5V | |
| 1.10 | Standard Discharge current | 260mA | |
| 1.11 | Standard Charge cut off current | 30mA | |
| 1.12 | PCB Protection trip current | Above 5A | |
| 1.13 | Max. Continuous discharge current | Max. 2.6A | |
| 1.14 | Cycle life | 70% capacity remained after 500 Cycles | Discharge:0.2CmA |
| 1.15 | Operation Temperature | 0°C~+45°C | Charge |
| 1.16 | | -20°C~+60°C | Discharge |
| 1.17 | Storage Temperature | -20°C~+60°C | Less than 1 month |
| 1.18 | | -20°C~+45°C | Less than 3 months |
| 1.19 | Weight | Max. 19g | |
| 1.20 | Size | (L)46.0mm*(D)14.60mm | |