

**Keppower Li Ion Rechargeable Battery
Protected 14500 3.6V 1500mAh P1450C4**

No.	Item	Details	Remarks
1.1	Product Name	Keppower Protected 14500 3.6V 1500mAh	
1.2	Supplier	Keppower Technology Co., Limited	
1.3	Cell	14500 3.6V 1500mAh	
1.4	Capacity	Min. 1400mAh; Normal: 1500mAh	Discharge:0.2CmA
1.5	Normal Volatge	3.60V	
1.6	Stanard Charge voltage	4.20V	
1.7	Standard Charge current	750mA	
1.8	Charge Time(Std.)	4 hours	
1.9	Standard Discharge Cut-off Voltage	2.5V	
1.10	Standard Discharge current	300mA	
1.11	Standard Charge cut off current	30mA	
1.12	PCB Protection trip current	Above 5A	
1.13	Max. Continuous Discharge Current	3A	
1.14	Cycle life	70% capacity remained after 500 Cycles	Discharge:0.2CmA
1.15	Operation Temperature	0°C~+45°C	Charge
1.16		-20°C~+60°C	Discharge
1.17	Storage Temperature	-20°C~+60°C	Less than 1 month
1.18		-20°C~+45°C	Less than 3 months
1.19	Weight	Max 22g	
1.20	Dimensions	(L)52.50mm*(D)14.60mm	