

roofrollfix

BUILDING SILICONE FOR LEAD ALTERNATIVES

Roof Roll Fix is an all-round, durable, flexible adhesive and sealant based on MS Polymer technology.

It provides excellent adhesion to non-porous surfaces, will bond to damp surfaces and is paintable with most paints. This product is odourless, neutral, and free of isocyanates.

Conforms to ISO 11600 F25 HM, EC No. 1935/2004 for materials intended to come into contact with food.



Applications

- Adhesion of EPDM to most substrates
- Gluing of products to bitumen
- Gluing and sealing of natural stone
- Waterproof construction adhesive
- Universal sealant for building sector

Directions

Surfaces must be clean and dust free.

Cut the cartridge seal and screw on the nozzle which can be cut to your required bead size.

Using a skeleton gun, apply the sealant into the gap or joint ensuring a good fill. If required, first place masking tape along edges and remove it within 10 minutes of application. For tooling, use a spatula or stick wetted with neutral soapy water within 10 minutes of application. For gluing applications apply adhesive in vertical lines at a distance apart of 30cm. Support the application for 24 hours until full curing has occurred.

Substrates

- Synthetic materials, EPDM and most plastics
- Stone substrates
- Metal Substrates
- Wooden substrates
- Storage and disposal

Dispose of empty containers in suitable containers. Store in a cool and dry area.
Shelf life of 12 months in unopened packaging at temperatures between +5°C and 25°C.

Harmonised Technical Specification

EN 15651-1:2012 | EN 15651-2:2012 | EN 15651-3:2012

Warranty & Guarantee

Den Braven warrants that its product complies, within its shelf life, to its specification.

Health and Safety recommendation

Avoid contact with skin and the eyes. Contains Bis (1.2.1.6.6-pentamethyl-4-piperidyl) sebacate.

N-(3-(trimethoxy-sily) propylethylenediamine).

N-(3-(dimethoxymethylsilyl) propylethyldiamine).

May produce an allergic reaction. Safety datasheet for professional users available on request.

Supplied in 310ml tubes. Dispose of empty packaging correctly.